

PRODUCT DATA SHEET

TSB 112

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tractor

TRA Code: F-2



Salient Features:

Wider Ribs:

- Provides Ease in steering.
- Better Manoeuvring.

High Strength Nylon Carcass:

- Provides longer tyre life.
- Trouble free service.



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm					Mixed Application						
		inch	inch					mm	mm	inch	inch	bar	static	10
								psi						
9.5L-15SL	8LB	251	782	356	2339	8PR 102 A8	2.5	1440	1080	920	800	720		
							36	3170	2380	2030	1760	1590		
							2.7	1500	1130	960	830	750		
							39	3300	2490	2110	1830	1650		
		9.9	30.8	14	92.1		3	1600	1200	1020	890	800		
							44	3520	2640	2250	1960	1760		
							3.3	1700	1280	1090	940	850		
							48	3740	2820	2400	2070	1870		
11L-15SL	8LB	279	813	369	2432	8PR 106 A8	2.3	1620	1220	1040	900	810		
							33	3570	2690	2290	1980	1780		
							2.5	1700	1280	1090	940	850		
							36	3740	2820	2400	2070	1870		
		11	32	14.5	95.7		2.7	1780	1340	1140	990	890		
							39	3920	2950	2510	2180	1960		
							3	1900	1430	1220	1050	950		
							44	4190	3150	2690	2310	2090		
10.00-16SL	8LB	274	894	404	2674	8PR 110 A8	2.3	1820	1370	1160	1010	910		
							33	4010	3020	2560	2220	2000		
							2.5	1920	1440	1230	1070	960		
							36	4230	3170	2710	2360	2110		
		10.8	35.2	15.9	105.3		2.7	2000	1500	1280	1110	1000		
							39	4410	3300	2820	2440	2200		
							3	2120	1590	1360	1180	1060		
							44	4670	3500	3000	2600	2330		
11.00-16SL	10LB	315	967	434	2892	8PR 114 A8	2.2	2060	1550	1320	1140	1030		
							32	4540	3410	2910	2510	2270		
							2.4	2160	1620	1380	1200	1080		
							35	4760	3570	3040	2640	2380		
		12.4	38.1	17.1	113.9		2.6	2260	1700	1450	1250	1130		
							38	4980	3740	3190	2750	2490		
							2.8	2360	1770	1510	1310	1180		
							41	5200	3900	3330	2890	2600		
11.00-16SL	10LB	315	967	434	2892	12PR 123 A8	3.2	2660	2000	1700	1480	1330		
							46	5860	4410	3740	3260	2930		
							3.5	2800	2100	1790	1550	1400		
							51	6170	4630	3940	3410	3080		
		12.4	38.1	17.1	113.9		3.8	2940	2210	1880	1630	1470		
							55	6480	4870	4140	3590	3240		
							4.15	3100	2330	1980	1720	1550		
							60	6830	5130	4360	3790	3410		

Note: All tyres confirm to ETRTO standards.

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

