

# PRODUCT DATA SHEET

## ***BOSS ML 35***

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** Tipper

**TRA Code:** ML



### ***Salient Features:***

**Non-directional Tread Design:**

Provides the best traction and stability in reverse and forward direction.

**Specially designed CPR compound:**

- Cooler running to prevent tread separation.
- Provides excellent puncture resistance.
- Ensures superior re-treadability.



# Technical Data



Tyre Size	PR	LI/SI	Recomm. Rim	Alternate Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity	
					SW	OD				Inflation Pressure	Max Load
					mm	mm					
					inch	inch					
10.00-20	18	144 G	7.5	7.00, 8.00	278	1073	487	3209	90	7.6	2800
					10.9	42.2	19.2	126.3	56	110	6170
11.00-20	18	146 G	8	7.5, 8.5	293	1104	500	3302	90	7.6	3000
					11.5	43.5	19.7	130	56	110	6610
12.00-20	18	150 F	8.5	8.0, 9.0	315	1146	517	3427	80	7.3	3350
					12.4	45.1	20.4	134.9	50	105	7385

Note: All tyres confirm to ETRTO standards

## Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

