

PRODUCT DATA SHEET

BOSS ML 36

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tipper

TRA Code: ML



Salient Features:

Non-directional Tread Design:

Provides the best traction and stability in reverse and forward direction.

Specially designed CPR compound:

- Cooler running to prevent tread separation.
- Provides excellent puncture resistance.
- Ensures superior re-treadability.



Technical Data



Tyre Size	PR	LI/SI	Recomm. Rim	Alternate Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity			
					SW	OD				Inflation Pressure	Max Load		
					mm	mm						bar	kg
					inch	inch						psi	lbs
12.00-24	20	155 F	8.5	8.0, 9.0	315	1247	568	3730	80	7.9	3875		
					12.4	49.1	22.4	146.8	50	115	8540		

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

