

PRODUCT DATA SHEET

FLB 680

Tyre Construction: Bias

Type: Tube Type

Main Applications: Forklift

TRA Code: NHS



Salient Features:

Unique Block Pattern Design:

- Ensures High traction.
- Optimum Load Distribution and wide footprint for Strong Stability.
- Enhanced performance on both indoor and outdoor Areas.



Technical Data



| Size | Recom. Rim | Unloaded Dimensions | | Static Load Radius | Rolling Circumference | PR | Inflation Pressure | Recommended load (kg) (lbs) | |
|---------|------------|---------------------|------|--------------------|-----------------------|----|--------------------|-----------------------------|-------------|
| | | SW | OD | | | | | Speed (kmph) (mph) | |
| | | mm | mm | | | | | Load Wheel | Steer Wheel |
| | | inch | inch | | | | | 15 kmph | 25 kmph |
| 5.00-8 | 3.00DX8 | 131 | 469 | 211 | 1403 | 10 | 10 | 1250 | – |
| | | 5.2 | 18.5 | 8.3 | 55.2 | | 145 | 2750 | – |
| 18×7-8 | 4.33RX8 | 168 | 465 | 210 | 1391 | 16 | 10 | 2130 | 1640 |
| | | 6.6 | 18.3 | 8.3 | 54.4 | | 145 | 4690 | 3610 |
| 6.00-9 | 4.00EX9 | 160 | 545 | 245 | 1630 | 10 | 8.5 | 1685 | 1280 |
| | | 6.3 | 21.5 | 9.6 | 64.2 | | 123 | 3710 | 2820 |
| 6.00-9 | 4.00EX9 | 160 | 545 | 245 | 1630 | 12 | 10 | 1875 | 1425 |
| | | 6.3 | 21.5 | 9.6 | 64.2 | | 145 | 4135 | 3140 |
| 21×8-9 | 6.00EX9 | 203 | 533 | 240 | 1594 | 14 | 9 | 2350 | 1785 |
| | | 8 | 21 | 9.4 | 62.8 | | 131 | 5180 | 3930 |
| 6.50-10 | 5.00FX10 | 178 | 597 | 268 | 1785 | 12 | 9 | 2150 | 1635 |
| | | 7 | 23.5 | 10.6 | 70.3 | | 131 | 4740 | 3600 |
| 7.00-12 | 5.00X12 | 192 | 683 | 308 | 2042 | 12 | 8.6 | 2720 | 2065 |
| | | 7.6 | 26.9 | 12.1 | 80.4 | | 125 | 5990 | 4550 |
| 7.00-12 | 5.00X12 | 192 | 683 | 308 | 2042 | 14 | 9 | 2790 | 2120 |
| | | 7.6 | 26.9 | 12.1 | 80.4 | | 125 | 6151 | 4674 |
| 300-15 | 8.0X15 | 300 | 840 | 380 | 2512 | 20 | 9.3 | 6575 | 4990 |
| | | 11.8 | 33.1 | 15 | 98.9 | | 135 | 14480 | 10990 |
| 7.00-15 | 6.00X15 | 203 | 762 | 348 | 2279 | 12 | 8.6 | 3150 | 2395 |
| | | 8.0 | 30 | 13.7 | 89.7 | | 125 | 6940 | 5280 |
| 7.50-15 | 6.00X15 | 215 | 808 | 367 | 2417 | 12 | 7.9 | 3490 | 2650 |
| | | 8.5 | 31.8 | 14.5 | 95.2 | | 115 | 7690 | 5840 |
| 8.25-15 | 6.50X15 | 236 | 847 | 383 | 2533 | 14 | 8.3 | 4255 | 3235 |
| | | 9.3 | 33.4 | 15.1 | 99.7 | | 120 | 9370 | 7130 |
| 28X9-15 | 7.00X15 | 221 | 706 | 325 | 2111 | 14 | 9.7 | 3415 | 2595 |
| | | 8.7 | 27.8 | 12.8 | 83.1 | | 141 | 7520 | 5720 |

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com