

PRODUCT DATA SHEET

FTR 170

Tyre Construction: Radial

Type: Tubeless

Main Applications: Tanker & Trailer

TRA Code: IMP



Salient Features:

Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications.
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm	mm	mm			Mixed Application							
		inch	inch	inch	inch			bar	Static	10	25	30	40	50	65
						psi		6	16	19	25	31	40		
480/45R17 SB	16.00	489	864	394	2584	140 D	1.0	2090	1640	1440	1370	1240	1100	910	
							15	4600	3610	3170	3020	2730	2420	2000	
							1.2	2350	1840	1610	1540	1390	1230	1020	
							17	5180	4050	3550	3390	3060	2710	2250	
							1.6	2880	2250	1980	1890	1700	1510	1250	
							23	6340	4960	4360	4160	3740	3330	2750	
							2.0	3290	2570	2260	2160	1940	1730	1430	
							29	7250	5660	4980	4760	4270	3810	3150	
	19.3	34.0	15.5	101.7	149 D	2.4	3800	2970	2610	2490	2240	2000	1650		
						35	8370	6540	5750	5480	4930	4410	3630		
						2.8	4300	3370	2950	2820	2540	2260	1870		
						41	9470	7420	6500	6210	5590	4980	4120		
						3.2	4720	3690	3240	3100	2790	2480	2050		
						46	10400	8130	7140	6830	6150	5460	4520		
						3.6	5200	4070	3570	3410	3070	2730	2260		
						52	11450	8960	7860	7510	6760	6010	4980		
500/50R17 SB	16.00	503	932	422	2787	149 D	2.8	5040	3940	3460	3310	2980	2650	2190	
							41	11100	8680	7620	7290	6560	5840	4820	
							3.2	5540	4340	3810	3640	3280	2920	2410	
							46	12200	9560	8390	8020	7220	6430	5310	
							3.6	6070	4750	4170	3990	3590	3190	2640	
	19.8	36.7	16.6	109.7	149 D	52	13370	10460	9190	8790	7910	7030	5810		
						4.0	6670	5220	4580	4380	3940	3510	2900		
						58	14690	11500	10090	9650	8680	7730	6390		
						5.0	7480	5850	5140	4910	4420	3930	3250		
						73	16480	12890	11320	10810	9740	8660	7160		

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm			bar	Static	10	25	30	40	50
		inch	inch	inch	inch	psi		6	16	19	25	31	40	
520/50R17 SB	16.00	516	952	430	2847	151 D	1.0	2600	2030	1790	1710	1540	1370	1130
							15	5730	4470	3940	3770	3390	3020	2490
							1.2	2920	2290	2010	1920	1730	1540	1270
							17	6430	5040	4430	4230	3810	3390	2800
							1.6	3590	2810	2460	2360	2120	1890	1560
							23	7910	6190	5420	5200	4670	4160	3440
							2.0	4090	3200	2810	2690	2420	2150	1780
							29	9010	7050	6190	5930	5330	4740	3920
							2.4	4740	3710	3250	3110	2800	2490	2060
	35	10440	8170	7160	6850		6170	5480	4540					
	2.8	5360	4190	3680	3520		3170	2820	2330					
	41	11810	9230	8110	7750		6980	6210	5130					
	3.2	5890	4610	4040	3870		3480	3100	2560					
	46	12970	10150	8900	8520		7670	6830	5640					
	3.6	6460	5060	4440	4240		3820	3400	2810					
	52	14230	11150	9780	9340		8410	7490	6190					
	4.0	7080	5540	4870	4650		4190	3730	3080					
	58	15590	12200	10730	10240		9230	8220	6780					
5.0	7940	6210	5450	5210	4690	4170	3450							
73	17490	13680	12000	11480	10330	9190	7600							
	20.3	37.5	16.9	112.1										

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm	Mixed Application											
		inch	inch	mm	mm			10	25	30	40	50	65		
				inch	inch	bar	Static	6	16	19	25	31	40		
						psi									
400/45R17.5 SB	14.00	414	805	363	2408	139 D	0.8	1400	1100	960	920	830	740	610	
							12	3080	2420	2110	2030	1830	1630	1340	
							1.2	1790	1400	1230	1180	1060	940	780	
							17	3940	3080	2710	2600	2330	2070	1720	
							1.6	2210	1730	1520	1450	1310	1160	960	
							23	4870	3810	3350	3190	2890	2560	2110	
							2.0	2510	1960	1720	1650	1480	1320	1090	
							29	5530	4320	3790	3630	3260	2910	2400	
							2.4	2900	2270	1990	1900	1710	1520	1260	
							35	6390	5000	4380	4190	3770	3350	2780	
	2.8	3290	2570	2260	2160		1940	1730	1430						
	41	7250	5660	4980	4760		4270	3810	3150						
	3.2	3610	2830	2480	2370		2140	1900	1570						
	46	7950	6230	5460	5220		4710	4190	3460						
	3.6	3980	3110	2730	2610		2350	2090	1730						
	52	8770	6850	6010	5750		5180	4600	3810						
	4.0	4350	3400	2990	2850		2570	2290	1890						
	58	9580	7490	6590	6280		5660	5040	4160						
	5.0	4900	3830	3370	3220		2900	2580	2130						
	73	10790	8440	7420	7090		6390	5680	4690						
6.0	5590	4370	3840	3670	3300	2940	2430								
87	12310	9630	8460	8080	7270	6480	5350								
		16.3	31.7	14.3	94.8										

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm	Mixed Application											
		inch	inch	inch	inch			bar	Static	10	25	30	40	50	65
								psi		6	16	19	25	31	40
500/60R22.5 SB	AG16.00	503	1172	533	3519	155 D	1.0	3270	2560	2240	2140	1930	1720	1420	
							15	7200	5640	4930	4710	4250	3790	3130	
							1.2	3660	2860	2510	2400	2160	1920	1590	
							17	8060	6300	5530	5290	4760	4230	3500	
							1.5	4280	3350	2940	2810	2530	2250	1860	
							22	9430	7380	6480	6190	5570	4960	4100	
							2.0	5130	4010	3520	3370	3030	2700	2230	
							29	11300	8830	7750	7420	6670	5950	4910	
	19.8	46.1	21.0	138.6	2.4		5910	4630	4060	3880	3500	3110	2570		
					35		13020	10200	8940	8550	7710	6850	5660		
					2.8		6690	5240	4600	4390	3960	3520	2910		
					41		14740	11540	10130	9670	8720	7750	6410		
					3.2		7360	5760	5060	4830	4350	3870	3200		
					46		16210	12690	11150	10640	9580	8520	7050		
					3.6		8100	6340	5560	5320	4790	4260	3520		
					52		17840	13960	12250	11720	10550	9380	7750		
560/45R22.5 SB	AG16.00	543	1075	493	3215	152 D	1.0	3010	2360	2070	1980	1780	1590	1310	
							15	6630	5200	4560	4360	3920	3500	2890	
							1.2	3380	2650	2320	2220	2000	1780	1470	
							17	7440	5840	5110	4890	4410	3920	3240	
							1.5	3930	3080	2700	2580	2330	2070	1710	
							22	8660	6780	5950	5680	5130	4560	3770	
							2.0	4740	3710	3250	3110	2800	2490	2060	
							29	10440	8170	7160	6850	6170	5480	4540	
	21.4	42.3	19.4	126.6	2.4		5450	4270	3740	3580	3220	2870	2370		
					35		12000	9410	8240	7890	7090	6320	5220		
					2.8		6190	4840	4250	4060	3660	3250	2690		
					41		13630	10660	9360	8940	8060	7160	5930		
					3.2		6810	5330	4680	4470	4030	3580	2960		
					46		15000	11740	10310	9850	8880	7890	6520		
					3.6		7480	5850	5140	4910	4420	3930	3250		
					52		16480	12890	11320	10810	9740	8660	7160		
4.0	8170	6390	5610	5360	4830	4300	3550								
58	18000	14070	12360	11810	10640	9470	7820								

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)										
		Speed (kmph) (mph)																
		Mixed Application																
		bar	Static					10	25	30	40	50	65					
psi	6	16		19	25	31	40											
		SW	OD															
		mm	mm	mm	mm													
		inch	inch	inch	inch													
560/60R22.5 SB	AG16.00	543	1249	565	3735	165 D	1.0	3910	3060	2690	2570	2310	2060	1700				
							15	8610	6740	5930	5660	5090	4540	3740				
							1.2	4420	3460	3030	2900	2610	2320	1920				
							17	9740	7620	6670	6390	5750	5110	4230				
							1.5	5130	4010	3520	3370	3030	2700	2230				
							22	11300	8830	7750	7420	6670	5950	4910				
							2.0	6160	4820	4230	4050	3640	3240	2680				
							29	13570	10620	9320	8920	8020	7140	5900				
	21.4	49.2	22.2	147.0	166 D	2.8	8050	6300	5530	5290	4760	4240	3500					
						41	17730	13880	12180	11650	10480	9340	7710					
						3.2	8860	6930	6080	5810	5240	4660	3850					
						46	19520	15260	13390	12800	11540	10260	8480					
						3.6	9730	7610	6680	6390	5750	5120	4230					
						52	21430	16760	14710	14070	12670	11280	9320					
						4.0	10650	8330	7320	6990	6300	5600	4630					
						58	23460	18350	16120	15400	13880	12330	10200					
580/65R22.5 SB	AG16.00	557	1326	597	3966	166 D	1.2	4990	3910	3430	3280	2950	2630	2170				
							17	10990	8610	7560	7220	6500	5790	4780				
							1.6	6100	4770	4190	4000	3600	3210	2650				
							23	13440	10510	9230	8810	7930	7070	5840				
							2.0	6970	5450	4790	4580	4120	3670	3030				
							29	15350	12000	10550	10090	9070	8080	6670				
							2.4	8050	6300	5530	5290	4760	4240	3500				
							35	17730	13880	12180	11650	10480	9340	7710				
	21.9	52.2	23.5	156.1	166 D	2.8	9110	7130	6260	5980	5390	4790	3960					
						41	20070	15700	13790	13170	11870	10550	8720					
						3.2	10030	7850	6890	6580	5930	5280	4360					
						46	22090	17290	15180	14490	13060	11630	9600					
						3.6	10990	8600	7550	7220	6500	5780	4780					
						52	24210	18940	16630	15900	14320	12730	10530					
						4.0	12190	9540	8370	8000	7210	6410	5300					
						58	26850	21010	18440	17620	15880	14120	11670					

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum .	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		Speed (kmph) (mph)													
		Mixed Application													
		bar	10					25	30	40	50	65			
psi	Static	6	16	19	25	31	40								
mm	mm	mm	mm	mm	mm	mm	mm								
inch	inch	inch	inch	inch	inch	inch	inch								
600/50R22.5 SB	AG20.00	611	1172	534	3505	159 D	1.0	3680	2880	2530	2420	2180	1940	1600	
							15	8110	6340	5570	5330	4800	4270	3520	
							1.2	4140	3240	2840	2720	2450	2180	1800	
							17	9120	7140	6260	5990	5400	4800	3960	
							1.5	4830	3780	3320	3170	2860	2540	2100	
							22	10640	8330	7310	6980	6300	5590	4630	
							2.0	5800	4540	3980	3810	3430	3050	2520	
							29	12780	10000	8770	8390	7560	6720	5550	
							2.4	6670	5220	4580	4380	3940	3510	2900	
	24.1	46.1	21.0	138.0	35	14690	11500	10090	9650	8680	7730	6390			
					2.8	7570	5920	5200	4970	4470	3980	3290			
					41	16670	13040	11450	10950	9850	8770	7250			
					3.2	8330	6520	5720	5470	4920	4380	3620			
					46	18350	14360	12600	12050	10840	9650	7970			
					3.6	9130	7150	6270	5990	5400	4800	3970			
					52	20110	15750	13810	13190	11890	10570	8740			
					4.0	10060	7880	6910	6610	5950	5290	4375			
					58	22160	17360	15220	14560	13110	11650	9640			
600/50R22.5 SB	AG20.00	611	1172	534	3505	167 D	1.0	4400	3440	3020	2890	2600	2310	1911	
							15	9690	7580	6650	6370	5730	5090	4210	
							1.2	4890	3830	3360	3210	2890	2570	2125	
							17	10770	8440	7400	7070	6370	5660	4680	
							1.5	5570	4360	3830	3660	3290	2930	2422	
							22	12270	9600	8440	8060	7250	6450	5330	
							2.0	6590	5160	4530	4330	3900	3470	2866	
							29	14520	11370	9980	9540	8590	7640	6310	
							2.4	7330	5740	5040	4820	4340	3860	3189	
	24.1	46.1	21.0	138.0	35	16150	12640	11100	10620	9560	8500	7020			
					2.8	8030	6280	5510	5270	4750	4220	3490			
					41	17690	13830	12140	11610	10460	9300	7690			
					3.2	8680	6790	5960	5700	5130	4570	3773			
					46	19120	14960	13130	12560	11300	10070	8310			
					3.6	9300	7280	6390	6100	5500	4890	4042			
					52	20480	16040	14070	13440	12110	10770	8900			
					4.0	9890	7740	6790	6490	5850	5200	4299			
					58	21780	17050	14960	14300	12890	11450	9470			
5.0	11270	8820	7740	7400	6660	5930	4899								
								73	24820	19430	17050	16300	14670	13060	10790
87	27620	21610	18960	18130	16320	14520	12000								
								1.0	4400	3440	3020	2890	2600	2310	1911

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm					Mixed Application							
		inch	inch					mm	mm	10	25	30	40	50	65
								bar	Static	6	16	19	25	31	40
620/40R22.5 SB	AG20.00	625	1068	491	3207	154 D	1.0	3170	2480	2180	2080	1880	1670	1380	
							15	6980	5460	4800	4580	4140	3680	3040	
							1.2	3570	2790	2450	2340	2110	1880	1550	
							17	7860	6150	5400	5150	4650	4140	3410	
							1.5	4160	3260	2860	2730	2460	2190	1810	
							22	9160	7180	6300	6010	5420	4820	3990	
							2.0	4990	3910	3430	3280	2950	2630	2170	
							29	10990	8610	7560	7220	6500	5790	4780	
							2.4	5770	4520	3970	3790	3410	3040	2510	
		35	12710	9960	8740		8350	7510	6700	5530					
		2.8	6530	5110	4490		4290	3860	3440	2840					
		41	14380	11260	9890		9450	8500	7580	6260					
		3.2	7200	5630	4950		4730	4260	3790	3130					
		46	15860	12400	10900		10420	9380	8350	6890					
		3.6	7890	6170	5420		5180	4660	4150	3430					
		52	17380	13590	11940		11410	10260	9140	7560					
		4.0	8630	6750	5930		5660	5100	4540	3750					
		58	19010	14870	13060		12470	11230	10000	8260					
650/50R22.5 SB	AG20.00	645	1222	554	3655	163 D	1.2	4670	3650	3210	3070	2760	2460	2030	
							17	10290	8040	7070	6760	6080	5420	4470	
							1.6	5700	4460	3920	3740	3370	3000	2480	
							23	12560	9820	8630	8240	7420	6610	5460	
							2.0	6530	5110	4490	4290	3860	3440	2840	
							29	14380	11260	9890	9450	8500	7580	6260	
							2.4	7520	5890	5170	4940	4450	3960	3270	
							35	16560	12970	11390	10880	9800	8720	7200	
							2.8	8580	6710	5890	5630	5070	4510	3730	
		41	18900	14780	12970		12400	11170	9930	8220					
		3.2	9380	7340	6450		6160	5550	4940	4080					
		46	20660	16170	14210		13570	12220	10880	8990					
		3.6	10300	8060	7080		6760	6090	5420	4480					
		52	22690	17750	15590		14890	13410	11940	9870					
		4.0	11210	8780	7700		7360	6630	5900	4875					
		58	24690	19340	16960		16210	14600	13000	10740					

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm			10	25	30	40	50	65	
				inch	inch	bar	psi	Static	6	16	19	25	31	40
710/40R22.5 SB	AG24.00	726	1140	520	3410	165 D	1.2	4420	3460	3030	2900	2610	2320	1920
							17	9740	7620	6670	6390	5750	5110	4230
							1.6	5380	4210	3700	3530	3180	2830	2340
							23	11850	9270	8150	7780	7000	6230	5150
							2.0	6160	4820	4230	4050	3640	3240	2680
							29	13570	10620	9320	8920	8020	7140	5900
							2.4	7110	5560	4880	4670	4200	3740	3090
							35	15660	12250	10750	10290	9250	8240	6810
							2.8	8070	6320	5550	5300	4770	4250	3510
		41	17780	13920	12220		11670	10510	9360	7730				
		3.2	8860	6930	6080		5810	5240	4660	3850				
		46	19520	15260	13390		12800	11540	10260	8480				
		3.6	9730	7610	6680		6390	5750	5120	4230				
		52	21430	16760	14710		14070	12670	11280	9320				
		4.0	10670	8350	7330		7010	6310	5610	4640				
		58	23500	18390	16150		15440	13900	12360	10220				
		5.0	11850	9270	8140		7780	7000	6230	5150				
		73	26100	20420	17930		17140	15420	13720	11340				
710/45R22.5 SB	AG24.00	726	1212	550	3625	165 D	1.0	4350	3400	2990	2850	2570	2290	1890
							15	9580	7490	6590	6280	5660	5040	4160
							1.2	4900	3830	3370	3220	2900	2580	2130
							17	10790	8440	7420	7090	6390	5680	4690
							1.6	6000	4700	4120	3940	3550	3160	2610
							23	13220	10350	9070	8680	7820	6960	5750
							2.0	6850	5360	4710	4500	4050	3610	2980
							29	15090	11810	10370	9910	8920	7950	6560
							2.4	7910	6190	5440	5190	4680	4160	3440
		35	17420	13630	11980		11430	10310	9160	7580				
		2.8	8970	7020	6160		5890	5300	4720	3900				
		41	19760	15460	13570		12970	11670	10400	8590				
		3.2	9870	7720	6780		6480	5830	5190	4290				
		46	21740	17000	14930		14270	12840	11430	9450				
		3.6	10830	8480	7440		7110	6410	5700	4710				
		52	23850	18680	16390		15660	14120	12560	10370				
		4.0	11850	9270	8140		7780	7000	6230	5150				
		58	26100	20420	17930		17140	15420	13720	11340				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm		bar	Static	10	25	30	40	50	65
		inch	inch	inch	inch		psi		6	16	19	25	31	40
600/55R26.5 SB	AG20.00	611	1333	609	3987	165 D	1.0	4300	3370	2950	2820	2540	2260	1870
							15	9470	7420	6500	6210	5590	4980	4120
							1.2	4830	3780	3320	3170	2860	2540	2100
							17	10640	8330	7310	6980	6300	5590	4630
							1.5	5640	4410	3870	3700	3330	2960	2450
							22	12420	9710	8520	8150	7330	6520	5400
							2.0	6760	5290	4650	4440	4000	3560	2940
							29	14890	11650	10240	9780	8810	7840	6480
							2.4	7800	6100	5360	5120	4610	4100	3390
	35	17180	13440	11810	11280		10150	9030	7470					
	2.8	8860	6930	6080	5810		5240	4660	3850					
	41	19520	15260	13390	12800		11540	10260	8480					
	3.2	9730	7610	6680	6390		5750	5120	4230					
	46	21430	16760	14710	14070		12670	11280	9320					
	3.6	10670	8350	7330	7010		6310	5610	4640					
	52	23500	18390	16150	15440		13900	12360	10220					
	4.0	11850	9270	8140	7780		7000	6230	5150					
	58	26100	20420	17930	17140		15420	13720	11340					

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
								Mixed Application							
								bar	Static	10	25	30	40	50	65
										psi	6	16	19	25	31
650/55R26.5 SB	AG20.00	645	1389	632	4171	170 D	1.0	4880	3820	3350	3200	2880	2570	2120	
							15	10750	8410	7380	7050	6340	5660	4670	
							1.2	5470	4280	3760	3590	3240	2880	2380	
							17	12050	9430	8280	7910	7140	6340	5240	
							1.5	6390	5000	4390	4200	3780	3360	2780	
							22	14070	11010	9670	9250	8330	7400	6120	
							2.0	7680	6010	5280	5040	4540	4040	3340	
							29	16920	13240	11630	11100	10000	8900	7360	
	2.4	8860	6930	6080	5810		5240	4660	3850						
	35	19520	15260	13390	12800		11540	10260	8480						
	2.8	10030	7850	6890	6580		5930	5280	4360						
	41	22090	17290	15180	14490		13060	11630	9600						
	3.2	11040	8640	7580	7250		6530	5810	4800						
	46	24320	19030	16700	15970		14380	12800	10570						
	3.6	12120	9490	8330	7960		7170	6380	5270						
	52	26700	20900	18350	17530		15790	14050	11610						
4.0	13800	10800	9480	9060	8160	7260	6000								
58	30400	23790	20880	19960	17970	15990	13220								
650/55R26.5 SB	AG20.00	645	1389	632	4154	178 D	1.0	4880	3820	3350	3200	2880	2570	2120	
							15	10750	8410	7380	7050	6340	5660	4670	
							1.2	5470	4280	3760	3590	3240	2880	2380	
							17	12050	9430	8280	7910	7140	6340	5240	
							1.5	6390	5000	4390	4200	3780	3360	2780	
							22	14070	11010	9670	9250	8330	7400	6120	
							2.0	7680	6010	5280	5040	4540	4040	3340	
							29	16920	13240	11630	11100	10000	8900	7360	
	3.2	11040	8640	7580	7250		6530	5810	4800						
	46	24320	19030	16700	15970		14380	12800	10570						
	3.6	12120	9490	8330	7960		7170	6380	5270						
	52	26700	20900	18350	17530		15790	14050	11610						
	4.0	13270	10390	9120	8710		7850	6980	5770						
	58	29230	22890	20090	19190		17290	15370	12710						
	5.0	14930	11680	10250	9800		8830	7850	6490						
	73	32890	25730	22580	21590		19450	17290	14300						
6.0	17250	13500	11850	11330	10200	9080	7500								
87	38000	29740	26100	24960	22470	20000	16520								

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm			10	25	30	40	50	65	
		mm	mm	mm	mm	bar	Static	6	16	19	25	31	40	
		inch	inch	inch	inch	psi		6	16	19	25	31	40	
650/60R26.5 SB	AG20.00	655	1450	657	4354	180 D	1.0	5240	4100	3600	3440	3100	2760	2280
							15	11540	9030	7930	7580	6830	6080	5020
							1.2	5910	4630	4060	3880	3500	3110	2570
							17	13020	10200	8940	8550	7710	6850	5660
							1.5	6900	5400	4740	4530	4080	3630	3000
							22	15200	11890	10440	9980	8990	8000	6610
							2.0	8260	6460	5670	5420	4880	4340	3590
							29	18190	14230	12490	11940	10750	9560	7910
							2.8	10810	8460	7430	7100	6390	5690	4700
		41	23810	18630	16370		15640	14070	12530	10350				
		3.2	11890	9310	8170		7810	7030	6260	5170				
		46	26190	20510	18000		17200	15480	13790	11390				
		3.6	13040	10210	8960		8560	7710	6860	5670				
		52	28720	22490	19740		18850	16980	15110	12490				
		4.0	14280	11180	9810		9380	8450	7510	6210				
		58	31450	24630	21610		20660	18610	16540	13680				
		5.0	16080	12580	11040		10550	9510	8460	6990				
		73	35420	27710	24320		23240	20950	18630	15400				
6.0	18400	14400	12640	12080	10880	9680	8000							
87	40530	31720	27840	26610	23960	21320	17620							
650/65R26.5 SB	AG20.00	645	1519	685	4543	174 D	1.2	6050	4730	4160	3970	3580	3180	2630
							17	13330	10420	9160	8740	7890	7000	5790
							1.6	7380	5780	5070	4850	4370	3880	3210
							23	16260	12730	11170	10680	9630	8550	7070
							2.0	8740	6840	6000	5740	5170	4600	3800
							29	19250	15070	13220	12640	11390	10130	8370
							2.4	10070	7880	6920	6610	5960	5300	4380
							35	22180	17360	15240	14560	13130	11670	9650
							2.8	11430	8950	7850	7500	6760	6010	4970
		41	25180	19710	17290		16520	14890	13240	10950				
		3.2	12770	9990	8770		8380	7550	6720	5550				
		46	28130	22000	19320		18460	16630	14800	12220				
		3.6	14100	11030	9690		9260	8340	7420	6130				
		52	31060	24300	21340		20400	18370	16340	13500				
		4.0	15410	12060	10590		10120	9110	8110	6700				
		58	33940	26560	23330		22290	20070	17860	14760				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm	Mixed Application											
		inch	inch	mm	mm		bar	Static	10	25	30	40	50	65	
		mm	mm	mm	mm	psi		6	16	19	25	31	40		
650/65R26.5 SB	AG20.00	645	1519	685	4543	181 D	1.2	6050	4730	4160	3970	3580	3180	2630	
							17	13330	10420	9160	8740	7890	7000	5790	
							1.6	7380	5780	5070	4850	4370	3880	3210	
							23	16260	12730	11170	10680	9630	8550	7070	
							2.0	8740	6840	6000	5740	5170	4600	3800	
							29	19250	15070	13220	12640	11390	10130	8370	
							2.4	10070	7880	6920	6610	5960	5300	4380	
							35	22180	17360	15240	14560	13130	11670	9650	
	25.4	59.8	27.0	178.9	2.8		11430	8950	7850	7500	6760	6010	4970		
					41		25180	19710	17290	16520	14890	13240	10950		
					3.2		12770	9990	8770	8380	7550	6720	5550		
					46		28130	22000	19320	18460	16630	14800	12220		
					3.6		14100	11030	9690	9260	8340	7420	6130		
					52		31060	24300	21340	20400	18370	16340	13500		
					4.0		15460	12100	10620	10150	9140	8130	6720		
					58		34050	26650	23390	22360	20130	17910	14800		
5.0	18980	14850	13040	12460	11220	9980	8250								
73	41810	32710	28720	27440	24710	21980	18170								

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)							
		SW	OD					Speed (kmph) (mph)							
		mm	mm	Mixed Application											
		inch	inch	mm	mm			bar	Static	10	25	30	40	50	65
		mm	mm	inch	inch	psi		6	16	19	25	31	40		
710/50R26.5 SB	AG24.00	726	1383	629	4136	170 D	0.8	4350	3400	2990	2850	2570	2290	1890	
							12	9580	7490	6590	6280	5660	5040	4160	
							2.4	9320	7290	6400	6120	5510	4900	4050	
							35	20530	16060	14100	13480	12140	10790	8920	
							2.8	10560	8260	7250	6930	6240	5550	4590	
							41	23260	18190	15970	15260	13740	12220	10110	
	28.6	54.4	24.8	162.8	3.2		11620	9090	7980	7630	6870	6110	5050		
					46		25590	20020	17580	16810	15130	13460	11120		
					3.6		12770	9990	8770	8380	7550	6720	5550		
					52		28130	22000	19320	18460	16630	14800	12220		
					4.0		13800	10800	9480	9060	8160	7260	6000		
					58		30400	23790	20880	19960	17970	15990	13220		
750/45R26.5 SB	AG24.00	754	1349	615	4035	170 D	1.0	5110	4000	3510	3350	3020	2690	2220	
							15	11260	8810	7730	7380	6650	5930	4890	
							1.2	5730	4480	3930	3760	3390	3010	2490	
							17	12620	9870	8660	8280	7470	6630	5480	
							1.5	6690	5240	4600	4390	3960	3520	2910	
							22	14740	11540	10130	9670	8720	7750	6410	
							2.0	8030	6280	5510	5270	4750	4220	3490	
							29	17690	13830	12140	11610	10460	9300	7690	
							2.4	9250	7240	6350	6070	5470	4860	4020	
							35	20370	15950	13990	13370	12050	10700	8850	
							2.8	10490	8210	7200	6890	6200	5520	4560	
							41	23110	18080	15860	15180	13660	12160	10040	
	3.2	11520	9020	7920	7570		6810	6060	5010						
	46	25370	19870	17440	16670		15000	13350	11040						
	3.6	12670	9920	8710	8320		7490	6670	5510						
	52	27910	21850	19190	18330		16500	14690	12140						
	4.0	13800	10800	9480	9060		8160	7260	6000						
	58	30400	23790	20880	19960		17970	15990	13220						

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm		10	25	30	40	50	65		
				inch	inch	bar	psi	Static	6	16	19	25	31	40
800/45R26.5 SB	AG28.00	828	1393	634	4183	174 D	1.0	5640	4410	3870	3700	3330	2960	2450
							15	12420	9710	8520	8150	7330	6520	5400
							1.2	6330	4950	4350	4150	3740	3330	2750
							1.7	13940	10900	9580	9140	8240	7330	6060
							1.5	7380	5780	5070	4850	4370	3880	3210
							2.2	16260	12730	11170	10680	9630	8550	7070
		2.0	8860	6930	6080		5810	5240	4660	3850				
		2.9	19520	15260	13390		12800	11540	10260	8480				
		2.4	10210	7990	7020		6700	6040	5370	4440				
		3.5	22490	17600	15460		14760	13300	11830	9780				
		2.8	11590	9070	7960		7610	6850	6100	5040				
		4.1	25530	19980	17530		16760	15090	13440	11100				
		3.2	12740	9970	8750		8370	7530	6700	5540				
		4.6	28060	21960	19270		18440	16590	14760	12200				
		3.6	13980	10940	9610		9180	8270	7360	6080				
		5.2	30790	24100	21170		20220	18220	16210	13390				
		4.0	15410	12060	10590		10120	9110	8110	6700				
		5.8	33940	26560	23330		22290	20070	17860	14760				
600/60R30.5 SB	AG20.00	611	1495	684	4471	173 D	1.2	5570	4360	3820	3650	3290	2930	2420
							1.7	12270	9600	8410	8040	7250	6450	5330
							1.6	6810	5330	4680	4470	4030	3580	2960
							2.3	15000	11740	10310	9850	8880	7890	6520
							2.0	7800	6100	5360	5120	4610	4100	3390
							2.9	17180	13440	11810	11280	10150	9030	7470
		2.4	8990	7040	6180		5900	5320	4730	3910				
		3.5	19800	15510	13610		13000	11720	10420	8610				
		2.8	10190	7970	7000		6690	6020	5360	4430				
		4.1	22440	17560	15420		14740	13260	11810	9760				
		3.2	11200	8770	7690		7350	6620	5890	4870				
		4.6	24670	19320	16940		16190	14580	12970	10730				
		3.6	12310	9630	8450		8080	7280	6470	5350				
		5.2	27110	21210	18610		17800	16040	14250	11780				
		4.0	13480	10550	9260		8850	7970	7090	5860				
		5.8	29690	23240	20400		19490	17560	15620	12910				
		5.0	14950	11700	10270		9820	8840	7870	6500				
		7.3	32930	25770	22620		21630	19470	17330	14320				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)																			
		SW	OD					Speed (kmph) (mph)																			
		mm	mm	Mixed Application																							
		inch	inch	mm	mm		bar	10	25	30	40	50	65														
		psi	Static	6	16		19	25	31	40																	
710/50R30.5 SB	AG20.00	686	1485	680	4441	176 D	2.8	11250	8800	7730	7380	6650	5920	4890													
							41	24780	19380	17030	16260	14650	13040	10770													
							3.2	12370	9680	8500	8120	7320	6510	5380													
							46	27250	21320	18720	17890	16120	14340	11850													
							3.6	13590	10640	9340	8920	8040	7150	5910													
	27.0	58.5	26.8	174.8	52		29930	23440	20570	19650	17710	15750	13020														
					4.0		14880	11650	10220	9770	8800	7830	6470														
					58		32780	25660	22510	21520	19380	17250	14250														
					4.4		16330	12780	11220	10720	9660	8590	7100														
					64		35970	28150	24710	23610	21280	18920	15640														
750/60R30.5 SB	AG24.00	754	1675	759	5010	181 D	2.4	12740	9970	8750	8370	7530	6700	5540													
							35	28060	21960	19270	18440	16590	14760	12200													
							2.8	14420	11290	9910	9470	8530	7590	6270													
							41	31760	24870	21830	20860	18790	16720	13810													
							3.2	15870	12420	10900	10420	9380	8350	6900													
	29.7	65.9	29.9	197.2	46		34960	27360	24010	22950	20660	18390	15200														
					3.6		17410	13630	11960	11430	10300	9160	7570														
					52		38350	30020	26340	25180	22690	20180	16670														
					4.0		18980	14850	13040	12460	11220	9980	8250														
					58		41810	32710	28720	27440	24710	21980	18170														
750/60R30.5 (SB) WS	AG24.00	780	1675	759	5010	181 D	1.2	7890	6170	5420	5180	4660	4150	3430													
							17	17380	13590	11940	11410	10260	9140	7560													
							1.6	9640	7540	6620	6330	5700	5070	4190													
							23	21230	16610	14580	13940	12560	11170	9230													
							2.0	11040	8640	7580	7250	6530	5810	4800													
							30.7	65.9	29.9	197.2	29	24320	19030	16700	15970	14380	12800	10570									
											2.4	12740	9970	8750	8370	7530	6700	5540									
											35	28060	21960	19270	18440	16590	14760	12200									
											2.8	14420	11290	9910	9470	8530	7590	6270									
											41	31760	24870	21830	20860	18790	16720	13810									
		46	3.2	15870	12420		10900	10420	9380	8350	6900	46	34960	27360	24010	22950	20660	18390	15200								
																				3.6	17410	13630	11960	11430	10300	9160	7570
																				52	38350	30020	26340	25180	22690	20180	16670
																				4.0	18980	14850	13040	12460	11220	9980	8250
																				58	41810	32710	28720	27440	24710	21980	18170

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		Speed (kmph) (mph)												
		Mixed Application												
		bar	Static					10	25	30	40	50	65	
		psi						6	16	19	25	31	40	
mm	mm	mm	mm	mm	mm	mm	mm							
inch	inch	inch	inch	inch	inch	inch	inch							
800/45R30.5 SB	AG24.00	788	1495	684	4471	176 D	1.2	6760	5290	4650	4440	4000	3560	2940
							17	14890	11650	10240	9780	8810	7840	6480
							1.6	8280	6480	5690	5440	4900	4360	3600
							23	18240	14270	12530	11980	10790	9600	7930
							2.0	9480	7420	6510	6220	5600	4990	4120
							29	20880	16340	14340	13700	12330	10990	9070
							2.4	10930	8550	7510	7170	6460	5750	4750
							35	24070	18830	16540	15790	14230	12670	10460
	31.0	58.9	26.9	176.0	2.8		12400	9700	8520	8140	7330	6520	5390	
					41		27310	21370	18770	17930	16150	14360	11870	
					3.2		13620	10660	9350	8940	8050	7160	5920	
					46		30000	23480	20590	19690	17730	15770	13040	
					3.6		14950	11700	10270	9820	8840	7870	6500	
					52		32930	25770	22620	21630	19470	17330	14320	
					4.0		16330	12780	11220	10720	9660	8590	7100	
					58		35970	28150	24710	23610	21280	18920	15640	

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
		mm	mm	Mixed Application										
		inch	inch	mm	mm			bar	Static	10	25	30	40	50
		inch	inch	inch	inch		psi	6	16	19	25	31	40	
850/50R30.5 SB	AG28.00	862	1625	738	4880	182 D	1.0	7250	5670	4980	4760	4280	3810	3150
							15	15970	12490	10970	10480	9430	8390	6940
							1.2	8140	6370	5590	5350	4810	4280	3540
							17	17930	14030	12310	11780	10590	9430	7800
							1.5	9500	7430	6530	6240	5620	5000	4130
							22	20930	16370	14380	13740	12380	11010	9100
							2.0	11390	8910	7820	7470	6730	5990	4950
							29	25090	19630	17220	16450	14820	13190	10900
	33.9	64.0	29.1	192.1	2.4		13130	10280	9020	8620	7770	6910	5710	
					35		28920	22640	19870	18990	17110	15220	12580	
					2.8		14900	11660	10240	9780	8810	7840	6480	
					41		32820	25680	22560	21540	19410	17270	14270	
					3.2		16380	12820	11250	10750	9680	8620	7120	
					46		36080	28240	24780	23680	21320	18990	15680	
					3.6		17990	14080	12360	11810	10640	9460	7820	
					52		39630	31010	27220	26010	23440	20840	17220	
800/60R32 SB	DW27B	818	1773	802	5303	185 D	1.2	8900	6970	6110	5840	5260	4680	3870
							17	19600	15350	13460	12860	11590	10310	8520
							1.6	10880	8510	7470	7140	6430	5720	4730
							23	23960	18740	16450	15730	14160	12600	10420
							2.0	12470	9760	8560	8180	7370	6560	5420
							29	27470	21500	18850	18020	16230	14450	11940
							2.4	14380	11250	9880	9440	8500	7560	6250
							35	31670	24780	21760	20790	18720	16650	13770
		32.2	69.8	31.6	208.8		2.8	16310	12760	11200	10710	9640	8580	7090
							41	35930	28110	24670	23590	21230	18900	15620
							3.2	17920	14020	12310	11760	10590	9430	7790
							46	39470	30880	27110	25900	23330	20770	17160
							3.6	19690	15410	13520	12930	11640	10360	8560
							52	43370	33940	29780	28480	25640	22820	18850
							4.0	21280	16650	14620	13970	12580	11190	9250
							58	46870	36670	32200	30770	27710	24650	20370

Note: SB – Steel Belted

Note: All tyres confirm to ETRTO standards.

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

