

PRODUCT DATA SHEET

IMB 165

Tyre Construction: Bias

Type: Tube Less

Main Applications: Dig Trencher

TRA Code: IMP



Salient Features:

Optimal Tread Design:

- Excellent traction & self-cleaning.
- High contact area for better stability and driving comfort.

Superior Carcass:

- Ensures better load carrying capacity.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / LI&SI	Inflation Pressure	Recommended Load kg, (lbs)			
		SW	OD					Speed kmph (mph)			
		mm	mm					mm	mm	bar	30
		inch	inch					inch	inch	psi	19
23X8.50-12	7JA,7.00-I-55; I-70;I-90	205	575	264	1720	6 PR 89 A6	2.3	580			
		8.1	22.6	10.4	67.7		33	1280			
26X12.00-12	10½ JA	308	655	297	1959	8 PR 112 A6	3	1120			
		12.1	25.8	11.7	77.1		44	2470			
26X12.00-12	10½ JA	308	655	297	1959	10 PR 117 A6	3.8	1285			
		12.1	25.8	11.7	77.1		55	2833			

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / LI&SI	Inflation Pressure	Recommended Load kg, (lbs)			
		SW	OD					Speed kmph (mph)			
		mm	mm					mm	mm	bar	50
		inch	inch					inch	inch	psi	31
29x12.50-15	10LB	312	755	345	2258	6 PR 98 B	2.1	750			
		12.3	29.7	13.6	88.9		30	1650			
31X15.50-15	13LB	390	800	363	2393	10 PR 121 B	4.1	1150			
		15.4	31.5	14.3	94.2		59	3200			

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ▪ E: enquiry@ascensotyres.com ▪ W: www.ascensotyres.com

