

PRODUCT DATA SHEET

MIB 406

Tyre Construction: Bias

Type: Tube Less

Main Applications: Backhoe Loader, Telehandler,
Grader, Wheel Loader

TRA Code: L-2/G-2



Salient Features:

Robust Solid Center Block pattern:

- Provides maximum ground contact.
- Ensures even load distribution.
- Suitable for rugged terrains
- The open shoulder lug pattern provides excellent traction.



Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LI/SI	Recommended Load	Inflation Pressure	Speed
				Static					
		SW	OD	Radius	mm				
		mm	mm	mm	mm				
inch	inch	inch	inch						
13.00-24	10	353	1278	581	3822	14 PR 170 A2	3000	3.25	40
							6600	48	25
		13.9	50.3	22.9	150.5		6000	5.25	10
							13200	77	7
14.00-24	10	377	1348	610	4032	16 PR 177 A2	3650	3.5	40
							8030	51	25
		14.8	53.1	24.0	158.7		7300	5.5	10
							16060	80	7
15.5-25	13	404	1278	583	3822	12 PR 168 A2	2650	2.5	40
							5830	37	25
		15.9	50.3	23.0	150.5		5600	4	10
							12320	59	7
17.5-25	14	445	1346	611	4026	16 PR 177 A2	3350	2.75	40
							7370	40	25
		17.5	53.0	24.1	158.5		7300	4.75	10
							16060	69	7
20.5-25	17	520	1492	672	4463	16 PR 181 A2	4000	2.3	40
							8800	33	25
		20.5	58.7	26.5	175.7		8250	3.5	10
							18188	51	7

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

