

# PRODUCT DATA SHEET

## PEB 720

**Tyre Construction:** Bias

**Type:** Tube Less/ Tube Type

**Main Applications:** Empty Container  
Handler

**TRA Code:** IND-3



### *Salient Features:*

**Highly Versatile and Superior Design:**

Superior traction and excellent performance.

**Deep Wide Tread Grooves:**

Reduce risk of groove cracks and heat buildup.

**Special Tread Compound:**

Minimizes wear and extends tire life significantly.



# Technical Data



Size	TT/TL	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)					
			SW	OD					Speed (kmph) (mph)					
			mm	mm					mm	mm	Bar	10	Bar	50
			inch	inch					inch	inch	psi	6	psi	31
14.00-24	TL	10.0WA/VA	375	1370	619	4098	28PR 188 A2	9.25	10000	6.5	5600			
			14.7	53.9	24.3	161.3		135	22000	95	12320			
14.00-24	TT	10.0W	375	1370	619	4098	28PR 188 A2	9.25	10000	6.5	5600			
			14.7	53.9	24.3	161.3		135	22000	95	12320			

Size	TT/TL	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)				
			SW	OD					Speed (kmph) (mph)				
			mm	mm					mm	mm	Bar	10	25
			inch	inch					inch	inch	psi	6	16
14.00-24	TL	10.0WA/VA	375	1370	619	4098	32	10	14175	13125			
			14.8	53.9	26.2	161.3		146	31185	28875			
16.00-25	TL	11.25/2.0	465	1485	666	4441	32	10	16875	15625			
			18.3	58.5	26.2	174.9		145	34450	37210			

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

