

PRODUCT DATA SHEET

SSB 330

Tyre Construction: Bias

Type: Tube Less

Main Applications: Skid Steer

TRA Code: R-4



Salient Features:

Solid Center Lug:

Provide wide contact & stability.

Open Shoulder Design:

Increases traction on loose off – road surfaces.

Rim Guard:

Protects the rim flange area against flats and wheel damage.



Technical Data



Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR & LSI	Recommended Load	Inflation Pressure	Speed		
		SW	OD								
		mm	mm				mm	mm	Kg	bar	Km/h
		in	in				in	in	lbs	psi	mph
10-16.5	8.25	264	773	356	2312	8PR 130 A2	1880	4.1	10		
							4140	60	6		
		10.4	30.4	14	91	10PR 134 A2	2140	5.2	10		
							4710	75	6		
12-16.5	9.75	307	831	380	2486	10PR 140 A2	2550	4.5	10		
							5600	65	6		
						12.1	32.7	15	97.9	12PR 145 A2	2900
		6393	80	6							
		14PR 147 A2	3075	6.2	10						
			6779	90	6						

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

