

PRODUCT DATA SHEET

SSB 331

Tyre Construction: Bias

Type: Tube Less

Main Applications: Skid Steer

TRA Code: R-4



Salient Features:

Deep tread & optimized space lugs:

Enhanced high traction & improves self-cleaning abilities

Extra strong Casing:

Higher load carrying capacity in all applications.

Special Tread Compound:

Higher tear & cut resistance in loading operations.



Technical Data

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR & LSI	Recommended Load	Inflation Pressure	Speed
		SW	OD						
		mm	mm						
		in	in						
23X8.50-12	7	213	574	263	1717	8PR 87 A8	550	3.4	40
		8.4	22.6	10.4	67.6		1200	49	25
23X8.50-12	7	213	574	263	1717	12PR 98 A8	750	6.2	40
		8.4	22.6	10.4	67.6		1653	90	25
26X12.00-12	10.5	307	655	297	1967	12PR 114 A8	1180	5.4	40
		12.1	25.8	11.7	77.4		2600	78	25
27x8.50-15	7	213	678	313	2028	8PR 102 A8	850	4.2	40
		8.4	26.7	12.3	79.8		1870	61	25
27x10.50-15	8.5	259	691	318	2067	8PR 105 A8	930	4.2	40
		10.2	27.2	12.5	81.4		2040	61	25
31X15.50-15	13	391	792	360	2369	10PR 125 A8	1660	4.2	40
		15.4	31.2	14.2	93.3		3640	61	25
10-16.5	8.25	264	773	356	2312	8PR 130 A2	1880	4.1	10
		10.4	30.4	14	91		4140	60	6
		264	773	356	2312	10PR 134 A2	2140	5.2	10
		10.4	30.4	14	91		4710	75	6

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LSI	Recommended Load	Inflation Pressure	Speed
		SW	OD	Static					
				Radius					
				mm					
in	mm	mm	mm	mm	Kg	bar	Km/h		
in	in	in	in	in	lbs	psi	mph		
12-16.5	9.75	307	831	380	2486	10PR 140 A2	2550	4.5	10
		12.1	32.7	15	97.9		5600	65	6
		307	831	380	2486	12PR 145 A2	2900	5.5	10
		12.1	32.7	15	97.9		6393	80	6
		307	831	380	2486	14PR 147 A2	3075	6.2	10
		12.1	32.7	15	97.9		6779	90	6
33X15.50-16.5	12	394	840	383	2522	12PR 148 A2	3150	4.1	10
		15.5	33.1	15.1	99.3		6940	59	6
14-17.5	10.5	349	921	419	2755	14PR 155 A2	3880	5.5	10
		13.7	36.3	16.5	108.5		8543	80	6
15-19.5	11.75	394	1019	464	3048	14PR 146 A8	3000	4.8	40
		15.5	40.1	18.3	120		6600	70	25

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

