

# PRODUCT DATA SHEET

## SSB 332

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Skid Steer

**TRA Code:** NHS (L-5)



### *Salient Features:*

**Extra Deep Tread Depth:**

Superior traction and long life

**Wider & Sturdier Blocks:**

High stability and puncture resistance

**Advanced Tread Compound:**

Excellent wear resistance in severe conditions.



# Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LI/SI	Recommended Load	Inflation Pressure	Speed
		SW	OD	Static					
		mm	mm	Radius					
		in	in	mm					
							Kg	bar	Km/h
							lbs	psi	mph
10-16.5	8.25	264	773	356	2312	10PR 134 A2	2120	5.2	10
		10.4	30.4	14	91		4675	75	6
12-16.5	9.75	307	831	380	2486	12PR 145 A2	2900	5.5	10
		12.1	32.7	15	97.9		6390	80	6
14-17.5	10.5	349	925	420	2766	14PR 155 A2	5.5	3875	10
		13.7	36.4	16.5	108.9		80	8543	6

**Note: All tyres confirm to ETRTO standards**

## Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

