

PRODUCT DATA SHEET

WLB 550

Tyre Construction: Bias

Type: Tube Less

Main Applications: Wheel Loader

TRA Code: E-3/L-3



Salient Features:

Robust Tread Design:

Generates maximum traction and resistance to slippage.

Strong Nylon Casing:

- Heavy load-carrying capacity
- Resistance to impacts.



Technical Data



Size	Recomm. Rim	Alternate Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load	Speed
			SW	OD						
			mm	mm	mm	mm		bar	kg	kmph
			inch	inch	inch	inch		psi	lbs	mph
15.5-25	12.00/1.3	-	394	1278	583	3838	12 PR 168A2/ 149B	4	5600	10
			15.5	50.3	22.9	151		2.5	3250	50
								58	12350	6
								36	7160	30
17.5-25	14.00/1.5	14.00/1.5DC, 14,00/1.3 DC, 13.00/1.4 DC	445	1348	612	4032	16 PR 177A2/ 158B	4.8	7300	10
			17.5	53.1	24.1	159		3	4250	50
								69	16100	6
								44	9370	30
17.5-25	14.00/1.5	-	445	1348	612	4032	20 PR 181A2/ 164B	5.8	8250	10
			17.5	53.1	24.1	159		4	5000	50
								83	18200	6
								58	11000	30
17.5-25	14.00/1.5	-	445	1348	612	4032	24 PR 188A2/ 168B	7	10000	10
			17.5	53.1	24.1	159		5.8	5600	50
								102	22000	6
								84	13550	30
17.5-25	14.00/1.5	-	445	1348	612	4032	32 PR	9.3	10900	10
			17.5	53.1	24.1	159		6.5	6700	50
								135	23980	6
								95	14740	30
20.5-25	17.00/2.0	17.00/1.7	520	1492	672	4463	16 PR 181A2/ 167B	3.5	8250	10
			20.5	58.7	26.5	176		2.8	5450	50
								51	18200	6
								40	12000	30
20.5-25	17.00/2.0	17.00/1.7	520	1492	672	4463	20 PR 186A2/ 170B	4.5	9500	10
			20.5	58.7	26.5	176		3.3	6000	50
								65	20900	6
								47	13200	30
23.5-25	19.5/1.5	19.5/2.5	597	1617	723	4837	20 PR 191A2/ 177B	3.8	10900	10
			23.5	63.7	28.5	190		3	7300	50
								54	24000	6
								44	16100	30
26.5-25	22.0/3.0	-	673	1750	777	5234	28 PR 203A2/ 188B	4.8	15500	10
			26.5	68.9	30.6	206		3.5	10000	50
								69	34180	6
								51	22050	30

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

