



LOAD CERTIFICATE : 11.2-38

Brand: ASCENSO

Tread Pattern : IRB 260

Tyre Construction: Bias

Type: Tube Less

Ply Rating : 6

Main Applications: Pivot , Irrigators

TRA Code: R1



Salient Features

Specially Designed Tread Pattern

Excellent traction and outstanding self-cleaning properties

Robust Nylon Carcass Construction

Enhances its ability to carry continuous heavy loads

Special Tread Compound

Minimizes wear and extends tire life significantly



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	mm	mm	Bar	10	10	20
in	in	in	in	in	Psi	6	6	12	6	16	20	25			
11.2-38	W10	284 11.2	1459 57.4	687 27.0	4364 171.8	6 PR 114 A8	1.5	1130	1590	1300	2440	1590	1300	1130	1060
							22	2490	3500	2860	5370	3500	2860	2490	2330
							1.6	1180	1650	1350	2530	1650	1350	1180	1100
							23	2600	3630	2970	5570	3630	2970	2600	2420
							1.7	1220	1710	1400	2620	1710	1400	1220	1140
							25	2690	3770	3080	5770	3770	3080	2690	2510
							1.8	1260	1770	1450	2710	1770	1450	1260	1180
							26	2780	3900	3190	5970	3900	3190	2780	2600

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com