



LOAD CERTIFICATES: 460/70R24

Brand: ASCENSO

Tread Pattern : MIR 220

Tyre Construction: Radial

LSI : 159 A8/B

Type: Tube Less

Main Applications: Wheel loaders, backhoe loaders and telehandlers

TRA Code : R-1



Salient Features

Robust Steel Belted Design:

- Improved Tread design- Provides better traction
- Enhanced Carcass- Stability for both On and Off-road operations.
- Excellent self-cleaning properties.
- Steel belted Construction for longer Tyre life.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)							Cyclic Applications	
								Constant Load								
		mm	mm					mm	mm	bar	Static	10	25	30	40	50
in	in	in	in	psi	6	16	19	25	31	6	9					
460/70R24	DW15L	465 18.3	1254 49.4	571 22.5	3750 147.6	159 A8/B	1.9	5470	2980	2520	2480	2380	2380	3570	3190	
							28	12050	6560	5550	5460	5240	5240	7860	7030	
							2	6350	3450	2930	2870	2760	2760	4140	3700	
							33	13990	7600	6450	6320	6080	6080	9120	8150	
							2.8	7430	4040	3420	3360	3230	3230	4850	4330	
							41	16370	8900	7530	7400	7110	7110	10680	9540	
							3.4	8740	4750	4050	3950	3800	3800	5700	5090	
							49	19250	10460	8920	8700	8370	8370	12560	11210	
							4	10060	5470	4640	4550	4375	4375	6560	5860	
							58	22160	12050	10220	10020	9640	9640	14450	12910	
							4.2	---	---	---	---	---	---	4570	6860	6120
							61	---	---	---	---	---	---	10070	15110	13480
							4.4	---	---	---	---	---	---	4760	7140	6380
64	---	---	---	---	---	---	10480	15730	14050							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com