



# LOAD CERTIFICATE: 18.4-26 IND

---

**Brand:** ASCENSO

**Tread Pattern :** BHB 311

**Ply Rating :** 12

**Tyre Construction:** Bias

**Type :** Tubeless

**Main Applications:** Backhoe Loader

**TRA Code :** R-1



## Salient Features

### **Robust Lug Design:**

Combination of robust lugs needed for industrial applications , combined with good self cleaning properties

### **Flat and Wider Tread:**

Excellent stability during vehicle operation

### **Special Tread Compound:**

Ensures protection from cut and punctures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg ( lbs)			
								Speed, km/h (mph)			
		SW	OD					Agriculture Use – Field	Agriculture Use – Road Transport		
		mm	mm						20	30	40
In	in	6	12	19	25						
18.4-26 IND	16	467	1450	656	4337	12 PR 156 A8	<b>2.5</b>	5000	4360	4160	<b>4000</b>
		18.4	57.1	25.8	170.7		36	11010	9600	9160	8810

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover