



LOAD CERTIFICATE: 550/60 – 22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 20

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)												
							Speed , km/h (mph)												
		SW	OD				Free rolling				Drive wheel								
		mm	mm				10	25	40	50	10	25	40	50					
In	in	in	in	in	in	Bar	10	25	40	50	Psi	6	16	25	31	6	16	25	31
550/60-22.5	16	553 21.7	1240 48.8	562 22.2	3709 146.0	20PR 171A8 FR 167B FR 158A8 DW 154B DW	2.7	7390	6280	5280	4750	5100	4330	3640	3276				
							39	16258	13816	11616	10450	11220	9526	8008	7207				
							2.9	7710	6560	5510	4960	5320	4520	3800	3420				
							42	16962	14432	12122	10912	11704	9944	8360	7524				
							3.2	8180	6950	5840	5260	5640	4800	4030	3627				
							46	17996	15290	12848	11572	12408	10560	8866	7979				
							3.5	8610	7320	6150	5540	5950	5060	4250	3825				
							51	18942	16104	13530	12188	13090	11132	9350	8415				

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com