



LOAD CERTIFICATE: 550/60-22.5 V

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/Sl or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm	Free rolling				Drive wheel							
		In	in	mm	mm		10	25	40	50	10	25	40	50	
				in	in		Bar	10	25	40	50	10	25	40	50
550/60-22.5 V	16	553 21.8	1240 48.8	562 22.1	3702 145.7	16 PR 166 A8 FR 162 B FR 154 A8 DW 150B DW	Psi	6	16	25	31	6	16	25	31
							2.3	6340	5390	4530	4080	4490	3820	3210	2889
							33	13948	11858	9966	8976	9878	8404	7062	6356
							2.5	6660	5660	4760	4280	4720	4010	3370	3033
							36	14652	12452	10472	9416	10384	8822	7414	6673
							2.7	6970	5930	4980	4480	4940	4200	3530	3177
							39	15334	13046	10956	9856	10868	9240	7766	6989
							3	7420	6310	5300	4770	5250	4460	3750	3375
44	16324	13882	11660	10494	11550	9812	8250	7425							

Note: All tyres confirm to ETRTO standards