



# LOAD CERTIFICATE: 12.5/80-15.3 (300/80-15.3)

**Brand:** ASCENSO

**Tread Pattern :** IMB 160

**Ply Rating :** 14

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Implements .

Balers and Trailer

**TRA Code :** I-2



## New Product Release

### **Optimum Implement Design:**

Minimises soil compaction and protects the grass land

### **Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)								
		SW	OD				Speed , km/h ( mph)								
		mm	mm	mm	mm	Free rolling				Drive wheel					
		In	in	in	in	LI/SI	Bar	10	25	40	50	10	25	40	50
						Psi	6	16	25	31	6	16	25	31	
12.5/80-15.3 (300/80-15.3 )	9	295 11.6	869 34.2	393 15.5	2600 102.4	14 PR 142 A8 FR 129 A8 DW	3.3	3180	2700	2270	2040	2230	1890	1590	1431
							48	6996	5940	4994	4488	4906	4158	3498	3148
							3.6	3350	2840	2390	2158	2340	1990	1670	1503
							52	7370	6248	5258	4730	5148	4378	3674	3307
							3.9	3500	2980	2500	2250	2450	2080	1750	1575
							57	7700	6556	5500	4950	5390	4576	3850	3465
							<b>4.3</b>	<b>3710</b>	<b>3150</b>	<b>2650</b>	<b>2390</b>	<b>2590</b>	<b>2200</b>	<b>1850</b>	<b>1665</b>
							<b>62</b>	<b>8162</b>	<b>6930</b>	<b>5830</b>	<b>5258</b>	<b>5698</b>	<b>4840</b>	<b>4070</b>	<b>3663</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification