



LOAD CERTIFICATE: 12.5/80-15.3
300/80-15.3

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 18

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements, Balers and Trailer

TRA Code : I-2



New Product Release Document

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm				Free rolling				Drive wheel				
		in	in				mm	mm	Bar	10	25	40	50	10	25
						LI/SI	Psi	6	16	25	31	6	16	25	31
12.5/80-15.3 (300/80-15.3)	9	295 11.6	869 34.2	393 15.5	2600 102.4	18 PR 151 A8 139 A8	3.3	3180	2700	2270	2040	2230	1890	1590	1431
							48	6996	5940	4994	4488	4906	4158	3498	3148
							3.6	3350	2840	2390	2158	2340	1990	1670	1503
							52	7370	6248	5258	4730	5148	4378	3674	3307
							3.9	3500	2980	2500	2250	2450	2080	1750	1575
							57	7700	6556	5500	4950	5390	4576	3850	3465
							6.75	4380	4070	3450	3110	3400	2870	2430	2910
97.9	10630	8950	7590	6840	7480	6310	5350	4820							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com