



LOAD CERTIFICATE: 15.0/70-18

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements.

Balers and Trailer

TRA Code : I-2



New Product Release

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

| Size | Rim | Unloaded Dimension | | SLR | RC | Free/ Drive Wheel | Recommended load , kg (lbs) | | | | | | | | |
|------------|-----|--------------------|-------------|-------------|---------------|---------------------------------------|------------------------------|--------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | | SW | OD | | | | Speed , km/h (mph) | | | | | | | | |
| | | mm | mm | mm | mm | Free rolling | | | | Drive wheel | | | | | |
| | | In | in | in | in | LI/SI | Bar | 10 | 25 | 40 | 50 | 10 | 25 | 40 | 50 |
| | | | | | | Psi | 6 | 16 | 25 | 31 | 6 | 16 | 25 | 31 | |
| 15.0/70-18 | 13 | 391 15.4 | 990 38.9 | 449 17.6 | 2961 116.5 | 16 PR 151 A8 FR 139 A8 DW | 3.3 | 4160 | 3530 | 2970 | 2670 | 2930 | 2490 | 2090 | 1881 |
| | | | | | | | 48 | 9152 | 7766 | 6534 | 5874 | 6446 | 5478 | 4598 | 4138 |
| | | | | | | | 3.6 | 4380 | 3720 | 3130 | 2820 | 3080 | 2620 | 2200 | 1980 |
| | | | | | | | 52 | 9636 | 8184 | 6886 | 6204 | 6776 | 5764 | 4840 | 4356 |
| | | | | | | | 3.9 | 4590 | 3900 | 3280 | 2950 | 3230 | 2750 | 2310 | 2079 |
| | | | | | | | 57 | 10098 | 8580 | 7216 | 6490 | 7106 | 6050 | 5082 | 4574 |
| | | | | | | | 4.25 | 4830 | 4110 | 3450 | 3110 | 3400 | 2890 | 2430 | 2187 |
| | | | | | | | 62 | 10626 | 9042 | 7590 | 6842 | 7480 | 6358 | 5346 | 4811 |

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification