



LOAD CERTIFICATE: 260/70-15.3

Brand: ASCENSO

Tread Pattern : IMB 161

Ply Rating : 10

Tyre Construction: Bias

Type: Tube Less

Main Applications: Balers and Trailer

TRA Code : I-2



Salient Features

Wider Footprint:

Minimises soil compaction and protects the grass land

Optimum Height to Width Ratio:

Ensures stability

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		Speed , km/h (mph)													
		Free rolling					Drive wheel								
		mm	mm				mm	mm	Bar	10	25	40	50	10	25
in	in	in	in	LI/SI	Psi	6	16	25	31	6	16	25	31		
260/70-15.3	9	268 10.5	753 29.6	345 13.5	2253 88.7	10 PR 122 A8 FR 110 A8 DW	2.5	1820	1550	1300	1170	1290	1090	920	828
							36	4004	3410	2860	2574	2838	2398	2024	1822
							2.7	1900	1620	1360	1220	1340	1140	960	864
							39	4180	3564	2992	2684	2948	2508	2112	1901
							2.9	1990	1690	1420	1280	1400	1190	1000	900
							42	4378	3718	3124	2816	3080	2618	2200	1980
							3.2	2100	1790	1500	1350	1480	1260	1060	954
							46	4620	3938	3300	2970	3256	2772	2332	2099

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com