



LOAD CERTIFICATE: 300/80-15.3

Brand: ASCENSO

Tread Pattern : IMB 161

Ply Rating : 14

Tyre Construction: Bias

Type: Tube Less

Main Applications: Balers and Trailer

TRA Code : I-2



Salient Features

Wider Footprint:

Minimises soil compaction and protects the grass land

Optimum Height to Width Ratio:

Ensures stability

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		Speed , km/h (mph)													
		Free rolling					Drive wheel								
		Bar	10				25	40	50	10	25	40	50		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm						
in	in	in	in	in	in	in	in	in	in						
LI/SI	Bar	10	25	40	50	10	25	40	50						
LI/SI	Psi	6	16	25	31	6	16	25	31						
300/80-15.3	9	295 11.6	869 34.2	392 15.4	2599 102.3	14 PR 139 A8 FR	2.8	2880	2450	2060	1850	-	-	-	-
							41	6336	5390	4532	4070	-	-	-	-
							3.1	3070	2610	2190	1970	-	-	-	-
							45	6754	5742	4818	4334	-	-	-	-
							3.4	3230	2750	2310	2080	-	-	-	-
							49	7106	6050	5082	4576	-	-	-	-
							3.7	3400	2890	2430	2190	-	-	-	-
							54	7480	6358	5346	4818	-	-	-	-

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com