



# LOAD CERTIFICATE: 340/55-16

**Brand:** ASCENSO

**Tread Pattern :** IMB 161

**Ply Rating :** 18

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Balers and Trailer

**TRA Code :** I-2



## Salient Features

### **Wider Footprint:**

Minimises soil compaction and protects the grass land

### **Optimum Height to Width Ratio:**

Ensures stability

### **Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)								
							Speed , km/h ( mph)								
		SW	OD				Free rolling				Drive wheel				
		mm	mm				mm	mm	mm	mm	mm	mm	mm	mm	
In	in	in	in	in	in	Bar	10	25	40	50	10	25	40	50	
						Psi	6	16	25	31	6	16	25	31	
340/55-16	11	343 13.5	780 30.7	358 14.0	2333 91.8	18 PR 140 A8 FR 128 A8 DW	3.6	2970	2520	2120	1910	2130	1810	1520	1368
							52	6534	5544	4664	4202	4686	3982	3344	3010
							4	3150	2680	2250	2030	2270	1930	1620	1458
							58	6930	5896	4950	4466	4994	4246	3564	3208
							4.4	3330	2830	2380	2140	2390	2030	1710	1539
							64	7326	6226	5236	4708	5258	4466	3762	3386
							<b>4.8</b>	3500	2980	<b>2500</b>	2250	2520	2140	<b>1800</b>	1620
70	7700	6556	5500	4950	5544	4708	3960	3564							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)