



# LOAD CERTIFICATE: 380/55-17

**Brand:** ASCENSO

**Tread Pattern :** IMB 161

**Ply Rating :** 10

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Balers and Trailer

**TRA Code :** I-2



## Salient Features

### **Wider Footprint:**

Minimises soil compaction and protects the grass land

### **Optimum Height to Width Ratio:**

Ensures stability

### **Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)								
		SW	OD				Speed , km/h ( mph)								
		mm	mm				Free rolling				Drive wheel				
		in	in				mm	mm	Bar	10	25	40	50	10	25
		mm	mm	mm	mm	Psi	6	16	25	31	6	16	25	31	
380/55-17	13	380 14.9	850 33.4	389 15.3	2543 100.1	Li/SI  10 PR 134 A8 FR 122 A8 DW	2	2550	2170	1820	1640	1810	1540	1290	1161
							29	5610	4774	4004	3608	3982	3388	2838	2554
							2.2	2690	2280	1920	1730	1900	1620	1360	1224
							32	5918	5016	4224	3806	4180	3564	2992	2693
							2.4	2830	2400	2020	1820	2000	1700	1430	1287
							35	6226	5280	4444	4004	4400	3740	3146	2831
							<b>2.6</b>	2970	2520	<b>2120</b>	1910	2100	1790	<b>1500</b>	1350
38	6534	5544	4664	4202	4620	3938	3300	2970							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)