



# LOAD CERTIFICATE: 400/60-15.5

**Brand:** ASCENSO

**Tread Pattern :** IMB 161

**Ply Rating :** 18

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Balers and Trailer

**TRA Code :** I-2



## Salient Features

### **Wider Footprint:**

Minimises soil compaction and protects the grass land

### **Optimum Height to Width Ratio:**

Ensures stability

### **Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)								
		SW	OD				Speed , km/h ( mph)								
		mm	mm				Free rolling				Drive wheel				
		in	in				mm	mm	Bar	10	25	40	50	10	25
						Li/SI	Psi	6	16	25	31	6	16	25	31
400/60-15.5	13	404 15.9	874 34.4	395 15.5	2614 102.9	18PR 149A8 FR 136A8 DW	3.4	3860	3280	2760	2480	2660	2260	1900	1710
							49	8492	7216	6072	5456	5852	4972	4180	3762
							3.7	4060	3450	2900	2610	2800	2380	2000	1800
							54	8932	7590	6380	5742	6160	5236	4400	3960
							4.1	4310	3670	3080	2770	2970	2520	2120	1908
							59	9482	8074	6776	6094	6534	5544	4664	4198
							4.5	4550	3870	3250	2930	3140	2670	2240	2016
65	10010	8514	7150	6446	6908	5874	4928	4435							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification