



IRB 260

New Product Release Document

Marketing Department.
October 12, 2021

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

New Product Release Document

List of Sizes

Release Month: October'21

Brand: ASCENSO

Tread Pattern : IRB 260

Tyre Construction: Bias

Type: Tube Less

Main Applications: Pivot , Irrigators

TRA Code: R1

Size	PR
11.2-24	6
14.9-24	8
11.2-38	6



Salient Features

Specially Designed Tread Pattern

Excellent traction and outstanding self-cleaning properties

Robust Nylon Carcass Construction

Enhances its ability to carry continuous heavy loads

Special Tread Compound

Minimizes wear and extends tire life significantly



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)												
		SW	OD					Speed , km/h(mph)												
								Field Operation			Road Operation; Not High and Sustained Torque									
		mm	mm					mm	mm	mm	mm	Bar	High Torque	Low Torque		Static	10	20	30	40
													6	6	12		6	16	20	25
in	in	in	in	in	in	Psi	6	6	12	6	16	20	25							
11.2-24	W10	284 11.2	1103 43.4	509 20.0	3299 129.9	6 PR 110 A8	1.5	1020	1430	1170	2190	1430	1170	1020	950					
							22	2250	3150	2580	4820	3150	2580	2250	2090					
							1.6	1060	1490	1220	2280	1490	1220	1060	990					
							23	2330	3280	2690	5020	3280	2690	2330	2180					
							1.7	1100	1550	1270	2370	1550	1270	1100	1030					
							25	2420	3410	2800	5220	3410	2800	2420	2270					
							1.8	1130	1590	1300	2440	1590	1300	1130	1060					
							26	2490	3500	2860	5370	3500	2860	2490	2330					
14.9-24	W13	378 14.9	1252 49.3	570 22.4	3745 147.4	8 PR 128 A8	1.5	1730	2430	1990	3730	2430	1990	1730	1620					
							22	3810	5350	4380	8220	5350	4380	3810	3570					
							1.6	1800	2520	2070	3860	2520	2070	1800	1680					
							23	3960	5550	4560	8500	5550	4560	3960	3700					
							1.7	1860	2610	2140	4000	2610	2140	1860	1740					
							25	4100	5750	4710	8810	5750	4710	4100	3830					
							1.8	1930	2700	2210	4140	2700	2210	1930	1800					
							26	4250	5950	4870	9120	5950	4870	4250	3960					

Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
11.2-38	W10	284 11.2	1459 57.4	687 27.0	4364 171.8	6 PR 114 A8	1.5	1130	1590	1300	2440	1590	1300	1130	1060
							22	2490	3500	2860	5370	3500	2860	2490	2330
							1.6	1180	1650	1350	2530	1650	1350	1180	1100
							23	2600	3630	2970	5570	3630	2970	2600	2420
							1.7	1220	1710	1400	2620	1710	1400	1220	1140
							25	2690	3770	3080	5770	3770	3080	2690	2510
							1.8	1260	1770	1450	2710	1770	1450	1260	1180
							26	2780	3900	3190	5970	3900	3190	2780	2600

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com