



LOAD CERTIFICATE : 17.5-25

Brand: ASCENSO

Tread Pattern : MIB 405

Ply Rating: 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Telehandler, Loader Grader

TRA Code: L2/G2



Salient Features

Robust Tread Design:

- Optimum traction on soil , sand , rock and gravel
- Higher contact area for better stability and minimum slippage

Abrasion Resistant Tread Compound:

- Ensures high tear and cut resistance



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommend Load Capacity (For Grader)		Recommended Load Capacity (For Loader/Telehandler)	
		SW	OD				Inflation Pressure	Speed , km/h(mph)	Inflation Pressure	Speed , km/h(mph)
		mm	mm				Bar	40	Bar	10
		in	in				Psi	25	Psi	7
17.5-25	14	445	1348	612	4032	16 PR	2.8	3350	4.8	7300
		17.5	53.1	24.1	158.7		40	7370	69	16060

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com