



# LOAD CERTIFICATE :15.5-25

**Brand:** ASCENSO

**Tread Pattern :** MIB 405

**Ply Rating:** 16

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Telehandler, Loader, Grader

**TRA Code:** L2/G2



## Salient Features

### **Robust Tread Design:**

- Optimum traction on soil, sand, rock and gravel
- Higher contact area for better stability and minimum slippage

### **Abrasion Resistant Tread Compound:**

- Ensures high tear and cut resistance



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommend Load Capacity (For Grader)		Recommended Load Capacity (For Loader/Telehandler)	
		SW	OD				Inflation Pressure	Speed , km/h(mph)	Inflation Pressure	Speed , km/h(mph)
		mm	mm	Bar	40		Bar	10		
		in	in	Psi	25		Psi	7		
15.5-25	12	394	1277	583	3820	16 PR	<b>3.2</b>	<b>3000</b>	<b>5.5</b>	<b>6900</b>
		15.5	50.3	23.0	150.4		<b>46</b>	<b>6600</b>	<b>80</b>	<b>15180</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)