



## LOAD CERTIFICATE : 23.1 - 26

**Brand:** ASCENSO

**Tread Pattern :** PCB 360

**Ply Rating :** 12

**Tyre Construction :** Bias

**Type :** Tubeless

**Main Applications:** Compactor and Combine Harvester

**TRA Code :** R-3



## Salient Features

### **Large Tread Area:**

Increases flotation and minimises  
Ground disturbance in soil compaction  
Operations

### **Optimized Diamond Lug Pattern**

#### **with Sipes:**

Reduces groove cracks and minimises  
slippage

### **Good Rubber Coverage on Tread Base:**

Ensures puncture and impact resistance  
thereby reducing downtime



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Infl. Pressure	Static	Recommended load, kg(lbs)							
		SW	OD						Speed, km/h ( mph)							
		mm	mm						Free Rolling				Drive Wheel			
		In	in						mm	mm	mm	mm	mm	mm	mm	mm
23.1-26	20	587 23.1	1581 62.2	710 28.0	4729 186.2	12 PR 162 A8	Bar	10	25	40	50	10	25	40	50	
							Psi	6	16	25	31	6	16	25	31	
							1.5	11160	6060	5140	4850	4410	5510	4670	4410	4010
							22	24552	13332	11308	10670	9702	12122	10274	9702	8822
							1.6	11590	6300	5340	5040	4590	5730	4850	4580	4170
							23	25498	13860	11748	11088	10098	12606	10670	10076	9174
1.7	<b>12020</b>	<b>6530</b>	<b>5540</b>	<b>5225</b>	<b>4750</b>	<b>5940</b>	<b>5040</b>	<b>4750</b>	<b>4320</b>							
25	<b>26444</b>	<b>14366</b>	<b>12188</b>	<b>11495</b>	<b>10450</b>	<b>13068</b>	<b>11088</b>	<b>10450</b>	<b>9504</b>							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)