



ASCENSO

never stop rising

LOAD CERTIFICATE : 23.1 - 26

Brand: ASCENSO

Tread Pattern : PCB 360

Ply Rating : 8

Tyre Construction : Bias

Type : Tubeless

Main Applications: Compactor and Combine Harvester

TRA Code : R-3



Salient Features

Large Tread Area:

Increases flotation and minimises
Ground disturbance in soil compaction
Operations

Optimized Diamond Lug Pattern

with Sipes:

Reduces groove cracks and minimises
slippage

Good Rubber Coverage on Tread Base:

Ensures puncture and impact resistance
thereby reducing downtime



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Infl. Pres.	Static	Recommended load, kg(lbs)							
		SW	OD						Speed, km/h (mph)							
		mm	mm						Free Rolling				Drive Wheel			
		in	in						10	25	40	50	10	25	40	50
		Bar														
		Psi	6	16	25	31	6	16	25	31						
23.1-26	20	587 23.1	1581 62.2	710 28.0	4729 186.2	8 PR 145A8	0.9	6530	3230	2730	2580	2350	3550	3010	2840	2580
							13	14366	7106	6006	5676	5170	7810	6622	6248	5676
							1	6950	3430	2900	2740	2490	3780	3200	3020	2750
							15	15290	7546	6380	6028	5478	8316	7040	6644	6050
							1.1	7340	3630	3070	2900	2640	3990	3380	3190	2900
							16	16148	7986	6754	6380	5808	8778	7436	7018	6380

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com