



## LOAD CERTIFICATE : 28L - 26

**Brand:** ASCENSO

**Tread Pattern :** PCB 360

**Ply Rating :** 16

**Tyre Construction :** Bias

**Type :** Tubeless

**Main Applications:** Compactor and Combine Harvester

**TRA Code :** R-3



## Salient Features

### **Large Tread Area:**

Increases flotation and minimises  
Ground disturbance in soil compaction  
Operations

### **Optimized Diamond Lug Pattern**

#### **with Sipes:**

Reduces groove cracks and minimises  
slippage

### **Good Rubber Coverage on Tread Base:**

Ensures puncture and impact resistance  
thereby reducing downtime



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Infl. Pres.	Static	Recommended load, kg(lbs)							
		SW	OD						Speed, km/h ( mph)							
		mm	mm						Free Rolling				Drive Wheel			
		in	in						10	25	40	50	10	25	40	50
		Bar														
		Psi	6	16	25	31	6	16	25	31						
28L-26	25	714	1591	715	4759	16 PR 173 A8	1.8	14630	7950	6740	6360	5790	7230	6130	5780	5260
							26	32186	17490	14828	13992	12738	15906	13486	12716	11572
							2	15550	8450	7170	6760	6150	7690	6520	6150	5600
							29	34210	18590	15774	14872	13530	16918	14344	13530	12320
							<b>2.2</b>	16450	8940	<b>7580</b>	7150	6510	8130	6890	<b>6500</b>	5920
							<b>32</b>	36190	19668	<b>16676</b>	15730	14322	17886	15158	<b>14300</b>	13024

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)