



LOAD CERTIFICATE: 12.4-32

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)										
		SW	OD					Speed , km/h(mph)										
								Field Operation			Road Operation; Not High and Sustained Torque							
		mm	mm					mm	mm	Bar	High Torque	Low Torque		Static	10	20	30	40
											mm	mm	mm		mm	mm	mm	mm
in	in	in	in	in	in	in	in	in	in	in	in	in						
12.4-32	W11L	315 12.4	1362 53.6	633 24.9	4074 160.4	8PR 125 A8	1.9	1630	2280	1870	3500	2280	1870	1630	1520			
							28	3590	5020	4120	7710	5020	4120	3590	3350			
							2.1	1720	2420	1980	3700	2420	1980	1720	1610			
							30	3790	5330	4360	8150	5330	4360	3790	3550			
							2.2	1770	2480	2030	3800	2480	2030	1770	1650			
							32	3900	5460	4470	8370	5460	4470	3900	3630			

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification