



## LOAD CERTIFICATE: 13.6-24

---

**Brand:** ASCENSO

**Tread Pattern :** TDB 120

**Ply Rating :** 8

**Main Applications:** 2WD Tractor

**TRA Code :** R-1



## Salient Features

### **Wider Lugs:**

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

### **Sturdy Sidewall Structure:**

Provides resistance to external damage

### **Strong Nylon Carcass:**

Safeguards the tyre against failures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	Bar	10	10	20	Static	10
in	in	in	in	Psi	6	6	12	6	16	20	25				
13.6-24	W12	345	1210	553	3619	8PR	1.9	1660	2330	1910	3570	2330	1910	1660	1550
		13.6	47.6	21.8	142.5	123 A8	28	3660	5130	4210	7860	5130	4210	3660	3410

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification