



LOAD CERTIFICATE: 13.6-28

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	mm	mm	Bar	10	10	20
in	in	in	in	in	in	Psi	6	6	12	6	16	20	25		
13.6-28	W12	345 13.6	1311 51.6	604 23.8	3921 154.4	8PR 125 A8	1.7	1660	2330	1910	3570	2330	1910	1660	1550
							25	3660	5130	4210	7860	5130	4210	3660	3410
							1.8	1710	2400	1970	3680	2400	1970	1710	1600
							26	3770	5290	4340	8110	5290	4340	3770	3520
							1.9	1770	2480	2030	3800	2480	2030	1770	1650
							28	3900	5460	4470	8370	5460	4470	3900	3630

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification