



LOAD CERTIFICATE : 14.9-26

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 10

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
14.9-26	W12	378 15	1316 51.80	601 23.60	3936 154.90	10 PR 129 A8	1.7	1710	2400	1970	3680	2400	1970	1710	1600
							25	3770	5290	4340	8110	5290	4340	3770	3520
							1.8	1770	2480	2030	3800	2480	2030	1770	1650
							26	3900	5460	4470	8370	5460	4470	3900	3630
							2	1870	2630	2150	4030	2630	2150	1870	1750
							29	4120	5790	4740	8880	5790	4740	4120	3850
							2.2	1980	2780	2280	4260	2780	2280	1980	1850
							32	4360	6120	5020	9380	6120	5020	4360	4070

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com