



LOAD CERTIFICATE : 16.9-24

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 12

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
16.9-24	W15L	429 16.9	1333 52.5	604 23.8	3987 157.0	12PR 143A8	2.2	2770	3890	3190	5960	3890	3190	2770	2590
							32	6100	8570	7030	13130	8570	7030	6100	5700
							2.4	2920	4090	3350	6270	4090	3350	2920	2725
							35	6430	9010	7380	13810	9010	7380	6430	6000

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover