



LOAD CERTIFICATE : 7.2-30

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 6

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
7.2-30	W6	183 7.2	1095 43.1	519 20.4	3275 128.9	6PR 96 A8	2.2	660	930	760	1430	930	760	660	620
							32	1450	2050	1670	3150	2050	1670	1450	1370
							2.4	700	980	800	1500	980	800	700	650
							35	1540	2160	1760	3300	2160	1760	1540	1430
							2.6	730	1020	840	1560	1020	840	730	680
							38	1610	2250	1850	3440	2250	1850	1610	1500
							2.8	760	1070	870	1630	1070	870	760	710
							41	1670	2360	1920	3590	2360	1920	1670	1560

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com