



LOAD CERTIFICATE : 9.5-32

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 6

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
9.5-32	W7	241 9.4	1251 49.2	587 23.1	3741 147.2	6PR 106 A8	1.7	900	1260	1030	1930	1260	1030	900	840
							25	1980	2780	2270	4250	2780	2270	1980	1850
							1.8	930	1310	1070	2000	1310	1070	930	870
							26	2050	2890	2360	4410	2890	2360	2050	1920
							1.9	960	1350	1110	2070	1350	1110	960	900
							28	2110	2970	2440	4560	2970	2440	2110	1980
							2.1	1020	1430	1170	2190	1430	1170	1020	950
							30	2250	3150	2580	4820	3150	2580	2250	2090

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com