



LOAD CERTIFICATE: 23.1-26

Brand: ASCENSO

Tread Pattern : TDB 123

Ply Rating : 16

Tyre Construction : Bias

Type : Tube Type

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Unique 23 Degree Lug Design:

Excellent ground contact , unbeatable traction , comfortable ride

Strong Nylon Carcass:

Safeguards the tyre against failures

Special Tread Compound:

Ensures longer tyre life



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
23.1-26	DW20	587 23.1	1605 63.2	720 28.3	4801	16PR	1.8	4060	5690	4660	8720	5690	4660	4060	3790
							26	8940	12530	10260	19210	12530	10260	8940	8350
							1.9	4180	5870	4810	8990	5870	4810	4180	3910
							28	9210	12930	10590	19800	12930	10590	9210	8610
							2.1	4440	6230	5100	9550	6230	5100	4440	4150
							30	9780	13720	11230	21040	13720	11230	9780	9140
							2.3	4680	6560	5380	10060	6560	5380	4680	4375
							33	10310	14450	11850	22160	14450	11850	10310	9640

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com