



LOAD CERTIFICATES : 580/70R38

Brand: ASCENSO

Tread Pattern : TDR 700

Tyre Construction: Radial

LSI: 180 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
								Mixed application								
								Bar	Static	10	25	30	40	50	65	
		mm	mm	mm	mm		Psi									
		in	in	in	in											
580/70 R 38	DW 18	577 22.72	1827 71.9	839 33.0	5465 215.2	180 D	2.5	9340	6090	4810	4670	4450	4260	4060		
							36	20570	13410	10590	10290	9800	9380	8940		
							3	11160	7280	5750	5580	5310	5090	4850		
							45	24580	16040	12670	12290	11700	11210	10680		
							3.8	13270	8660	6840	6640	6320	6060	5770		
							55	29230	19070	15070	14630	13920	13350	12710		
							4.7	15990	10430	8240	7990	7610	7300	6950		
							68	35220	22970	18150	17600	16760	16080	15310		
							5.5	18400	12000	9480	9200	8760	8400	8000		
80	40530	26430	20880	20260	19300	18500	17620									

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com