



LOAD CERTIFICATE: 320/85R38

Brand: ASCENSO

Tread Pattern : TDR 850

Tyre Construction: Radial

LSI : 143D

Type: Tube Less

Main Applications: 2WD & 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	Static	10	25	30	40	50
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
in	in	in	in	in	in	in	Psi	6	16	19	25	31	40	
320/85 R38	W11	319 12.5	1509 59.4	707 27.8	4513 177.6	143 D	1.6	3290	2150	1690	1640	1570	1500	1430
							23	7250	4740	3720	3610	3460	3300	3150
							2	3890	2540	2000	1940	1850	1770	1690
							29	8570	5590	4410	4270	4070	3900	3720
							2.5	4620	3020	2380	2310	2200	2110	2010
							36	10180	6650	5240	5090	4850	4650	4430
							3.1	5520	3600	2840	2760	2630	2520	2400
							45	12160	7930	6260	6080	5790	5550	5290
							3.6	6270	4090	3230	3130	2980	2860	2725
							52	13810	9010	7110	6890	6560	6300	6000

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com