



LOAD CERTIFICATE: 380/85R28

Brand: ASCENSO

Tread Pattern : TDR 850

Tyre Construction: Radial

LSI : 133D

Type: Tube Less

Main Applications: 2WD & 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Mixed application									
								Bar	Static	10	25	30	40	50	65		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
in	in	in	in	in	in	in	Psi	Static	6	16	19	25	31	40	40	40	40
380/85 R28	W12	380 15.0	1357 53.4	622 24.5	4059 159.8	133 D	0.8	2990	1950	1540	1500	1420	1370	1300			
							12	6590	4300	3390	3300	3130	3020	2860			
							1.0	3430	2240	1770	1710	1630	1560	1490			
							15	7560	4930	3900	3770	3590	3440	3280			
							1.2	3860	2520	1990	1930	1840	1760	1680			
							17	8500	5550	4380	4250	4050	3880	3700			
							1.4	4300	2810	2220	2150	2050	1960	1870			
							20	9470	6190	4890	4740	4520	4320	4120			
							1.6	4740	3090	2440	2370	2260	2160	2060			
							23	10440	6810	5370	5220	4980	4760	4540			

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com