



LOAD CERTIFICATE: 520/85R38

Brand: ASCENSO

Tread Pattern : TDR 850

Tyre Construction: Radial

LSI : 155D

Type: Tube Less

Main Applications: 2WD & 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
		SW	OD					Mixed application						
		mm	mm					Bar	Static	10	25	30	40	50
in	in	in	in	Psi		6	16	19	25	31	40			
520/85R38	DW16L	516 20.3	1849 72.8	848 33.4	5530 217.7	155 D	0.8	5680	3710	2930	2840	2700	2590	2470
							12	12510	8170	6450	6260	5950	5700	5440
							1	6490	4230	3340	3240	3090	2960	2820
							15	14300	9320	7360	7140	6810	6520	6210
							1.2	7290	4760	3760	3650	3470	3330	3170
							17	16060	10480	8280	8040	7640	7330	6980
							1.4	8100	5280	4170	4050	3850	3700	3520
							20	17840	11630	9190	8920	8480	8150	7750
							1.6	8910	5810	4590	4460	4240	4070	3875
23	19630	12800	10110	9820	9340	8960	8540							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com