



LOAD CERTIFICATE: 11.00-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 10

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)										
		SW	OD					Speed, km/h(mph)										
		mm	mm	mm	mm		Mixed Application											
		in	in	in	In		Bar	Static	10	20	25	30	40					
				Psi	6	12	15		20	25								
11.00-16	W10L	315	967	435	2893	10PR	2.5	3390	2260	1560	1450	1250	1130					
							36	7470	4980	3440	3190	2750	2490					
							2.7	3540	2360	1630	1510	1310	1180					
							39	7800	5200	3590	3330	2890	2600					
							12.4	38.1	17.1	113.9	118 A8	3.0	3750	2500	1730	1600	1390	1250
							44	8260	5510	3810	3520	3060	2750					
							3.3	3960	2640	1820	1690	1470	1320					
							48	8720	5810	4010	3720	3240	2910					

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification