



## LOAD CERTIFICATE: 4.00-19

**Brand:** ASCENSO

**Tread Pattern :** TSB 110

**Ply Rating :** 6

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code:** F2



## Salient Features

### **Wider Centre Rib:**

Ease in steering & prevents damage to the grass land

### **High Strength Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h(mph)							
		mm	mm					Mixed Application							
		in	in					mm	mm	mm	mm	mm	mm	mm	mm
		in	in					in	in	in	in	in	in	in	in
4.00-19	3.00D	112	717	338	2145	6 PR	2.7	810	540	370	350	300	270		
							39	1780	1190	810	770	660	590		
							3.0	870	580	400	370	320	290		
							44	1920	1280	880	810	700	640		
		4.4	28.2	13.3	84.5	72 A8	3.3	930	620	430	400	340	310		
							48	2050	1370	950	880	750	680		
							3.6	980	650	450	420	360	325		
							52	2160	1430	990	930	790	720		

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover