



LOAD CERTIFICATE: 5.50-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 6

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
								Speed, km/h(mph)					
								Mixed Application					
		SW	OD					Static	10	20	25	30	40
mm	mm	Bar											
		in	in	mm	mm	Psi							
5.50-16	4.00E	150	713	330	2133	6PR	2.2	1020	680	470	440	380	340
							32	2250	1500	1040	970	840	750
							2.6	1140	760	520	490	420	380
							38	2510	1670	1150	1080	930	840
		5.9	28.1	13.0	84.0	82 A8	3.0	1230	820	560	520	460	410
							44	2710	1810	1230	1150	1010	900
							3.85	1430	950	650	610	530	475
							56	3150	2090	1430	1340	1170	1050

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification