



LOAD CERTIFICATE: 7.50-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 10

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		Speed, km/h(mph)											
		Mixed Application											
		Bar	Static					10	20	25	30	40	
Psi	6	12		15	20	25							
7.50-16	5.50F	203	808	369	2417	10 PR 104 A8	3.6	2280	1520	1050	970	840	760
							52	5020	3350	2310	2140	1850	1670
							3.9	2400	1600	1100	1020	890	800
							57	5290	3520	2420	2250	1960	1760
		8.0	31.8	14.5	95.2		4.3	2550	1700	1170	1090	940	850
		62					5620	3740	2580	2400	2070	1870	
		4.75					2700	1800	1240	1150	1000	900	
		69					5950	3960	2730	2530	2200	1980	

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover