



LOAD CERTIFICATE: 4.50-16

Brand: ASCENSO

Tread Pattern : TSB 111

Ply Rating: 6

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code : F-2



Salient Features

Unique Dumbbell Pattern:

Reduces block tearing & shoulder block deformation

Strong Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
4.50-16	3.00D	122 4.8	655 25.8	306 12.0	1959 77.2	6 PR 74 A8	2.2	750	500	340	320	280	250
							32	1650	1100	750	700	620	550
							2.6	840	560	380	360	310	280
							38	1850	1230	840	790	680	620
							3.0	900	600	410	380	330	300
							44	1980	1320	900	840	730	660
							4.5	1130	750	510	480	420	375
							65	2490	1650	1120	1060	930	830

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification