



## LOAD CERTIFICATE: 5.50-16

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 6

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
5.50-16	4.00E	150 5.9	713 28.0	330 13.0	2133 84.0	6 PR 82 A8	2.2	1020	680	470	440	380	340
							32	2250	1500	1040	970	840	750
							2.6	1140	760	520	490	420	380
							38	2510	1670	1150	1080	930	840
							3.0	1230	820	560	520	460	410
							44	2710	1810	1230	1150	1010	900
							<b>3.85</b>	<b>1430</b>	<b>950</b>	<b>650</b>	<b>610</b>	<b>530</b>	<b>475</b>
							<b>56</b>	<b>3150</b>	<b>2090</b>	<b>1430</b>	<b>1340</b>	<b>1170</b>	<b>1050</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification