



LOAD CERTIFICATE: 6.00-19

Brand: ASCENSO

Tread Pattern : TSB 111

Ply Rating: 8

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code : F-2



Salient Features

Unique Dumbbell Pattern:

Reduces block tearing & shoulder block deformation

Strong Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
6.00-19	4.50E	165 6.5	814 32.0	376 14.8	2435 95.8	8 PR 91 A8	2.9	1560	1040	720	670	580	520
							42	3440	2290	1590	1480	1280	1150
							3.2	1650	1100	760	700	610	550
							46	3630	2420	1670	1540	1340	1210
							3.5	1740	1160	800	740	640	580
							51	3830	2560	1760	1630	1410	1280
							3.85	1850	1230	850	790	680	615
							56	4070	2710	1870	1740	1500	1350

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification